



## Catalog Number B22 Series

**Rainproof Air Conditioner Pullout Units:**  
Fused, Non-Fused, GFCI and Cable Whip.

**Agency Approvals:** UL Listed to UL 1429  
CSA Certification

### Features:

- NEMA 3R enclosure.
- Compact design but offers ample working space.
- Internal shield can be removed without tools.
- Specifications are printed on internal shield.
- Knockouts on back, bottom and both sides.
- Finger-safe construction.
- Padlockable.

## Metallic

**Ratings:** Single-Phase 2-Wire, 240Vac, 30 & 60A  
UL Guide WGEW

**Wire Range:** #14-3 AWG, Al/Cu

### Catalog Data

Main Rating	Catalog Number/Description	Maximum HP <sup>1</sup>		Approx. Dim. H x W x D (in.)
		120Vac	240Vac	
30A	B221-30F* Fused Disconnect (Class H or R)	1.5	3	8 3/4 x 5 1/2 x 32 1/2
30A	B221-30FGF Fused Disconnect with GFCI (Class H or R)	1.5	3	13 x 7 1/2 x 4 3/4
60A	B222-60F* Fused Disconnect (Class H or R)	3	10	8 3/4 x 5 3/4 x 32 1/2
60A	B222-60FGF Fused Disconnect with GFCI (Class H or R)	3	10	13 x 7 1/2 x 4 3/4
60A	B222-60NF Non-fused Disconnect	3	10	13 x 7 1/2 x 4 3/4
60A	B222-60NFGF Non-fused Disconnect with GFCI	3	10	11 1/4 x 6 1/2 x 4 1/2
60A	B222-60NFG12W** Non-fused Disconnect with 1/2 inch Cable Whip	3	10	14 3/4 x 12 1/2 x 4.5

\*Suitable for use as service equipment with optional field installed lug kit number B-DPOG.

<sup>1</sup>Rated with Edison ECNR and LENRK dual-element time-delay fuses.

\*\* Maximum 30 amp upstream overcurrent protection device, 1/2 inch harness device, #10 ground hot wire size, #10 flexible wire size, six feet of conduit, 1-90° and 1- straight non-metallic fitting.