



EMT Conduit

In-line HDG, 10'/length

Features

- In-Line Hot Dip Galvanized to prevent corrosion
- Smooth Interior with Slip-Coating makes wire-pulling easy and protects against damage to the conductors
- Conduit ends are cold galvanized treated to prevent corrosion
- cULus Listed to UL-797



Applications

- Indoor or outdoor use
- Provide mechanical protection for conductors

Standard Material

- Mild Strip Steel
- Galvanized exterior with slip-coating on interior

Certification

- UL Code #: E361993

Catalog Number	UPC	Trade Size in. (mm)	Bundle (ft)	Sling (ft)	Weight per 100'	Nominal OD (in)	Nominal ID (in)	Nominal Wall Thickness (in)
EMT-05	13820	1/2" (16)	100	2500	30	0.706	0.622	0.042
EMT-07	13824	3/4" (21)	100	2000	46	0.922	0.824	0.049
EMT-10	13826	1" (27)	50	1000	67	1.163	1.049	0.057
EMT-12	13828	1-1/4" (35)	50	500	101	1.510	1.380	0.065
EMT-15	13829	1-1/2" (41)	50	500	116	1.740	1.610	0.065
EMT-20	13830	2" (53)	30	510	148	2.197	2.067	0.065
EMT-25	13832	2-1/2" (63)	10	250	216	2.875	2.731	0.072
EMT-30	13833	3" (78)	10	200	263	3.500	3.356	0.072
EMT-35	13834	3-1/2" (91)	10	100	349	4.000	3.834	0.083
EMT-40	13835	4" (103)	10	100	393	4.500	4.334	0.083

Nesco Inc.

1039 Cardiff Blvd., Mississauga, ON L5S 1P4
 TF: (866) 466-3726 Tel: (905) 793-2218 Fax: (905) 793-2268
www.nescocanada.com