

# Product data sheet

Specifications

SQUARE D



Contactor, Definite Purpose, 40A,  
3 pole, 25 HP at 575VAC, 3 phase,  
110/120VAC coil at 50/60Hz, open

8910DPA43V02

## Main

Product or component type	Definite Purpose Contactor
[In] rated current	40 A
Number of Poles	3P
Pole contact composition	3 NO
Range of product	DPA

## Complementary

Motor power hp	3 hp 115 V AC, 1 phase 7.5 hp 230 V AC, 1 phase 10 hp 230 V AC, 3 phases 20 hp 460 V AC, 3 phases 25 hp 575 V AC, 3 phases
Locked rotor rated current	240 A 277 V AC 200 A 460 V AC 160 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Network number of phases	3 phases
Electrical connection	Quick connect terminals Box lugs
Height	2.31 in (58.67 mm) 2.31 in (58.70 mm)
Width	2.37 in (60.20 mm) 2.37 in (60.2 mm)
Depth	2.90 in (73.66 mm) 2.99 in (76 mm)
Net weight	0.99 lb(US) (0.45 kg) 0.99 lb(US) (0.45 kg)

## Environment

Product certifications	UL recognized CSA
------------------------	----------------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

<b>Package 1 Height</b>	2.60 in (6.6 cm)
<b>Package 1 Width</b>	3.10 in (7.87 cm)
<b>Package 1 Length</b>	4.30 in (10.92 cm)
<b>Package 1 Weight</b>	16.80 oz (476.28 g)

## Offer Sustainability

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

Approximate Dimensions

