

MICRO COMPACT SERIES

ODD-70-1 | ODD-90-1 | ODD-110-1

HIGHLIGHTS

Next Generation Single Speed DC Motor Compact Series

- Ultra Silent, High Performance
- Very quiet fan for ceiling or wall mounted Hold
- Comes with a capacitor start motor known for its high efficiency and long lasting reliability



SPECIFICATIONS

HANGER BARS NOT INCLUDED - SOLD SEPARATELY

Model	ODD-70-1		ODD-90-1		ODD-110-1	
Airflow (CFM)	75	62	95	78	112	94
Sound Level (Sones)	0.4	1.1	0.7	1.2	1	1.3
Static Pressure (In wg)	0.1	0.25	0.1	0.25	0.1	0.25
Duct size (inch)	4"					
Motor Power(W)	4.5W	7.4W	7.2W	9.0W	9.8W	10.8W
Housing dimension (in)	9"x9"x5 3/4"					
Grille dimension (in)	11 7/8"x11 3/8"					
Voltage	120V/60HZ					
Efficacy (CFM/W)	16.6	8.3	13.1	8.6	11.4	8.7
Speed	70CFM		90CFM		110CFM	
Housing Discharge	Galvanized steel Horizontal					
Warranty	5 Years					
Case Quantities	6					

HOUSING

- Made of rugged 26 GA galvanized steel
- Detachable 4 inch polymeric collar which includes a light weight built-in back draft damper

MOTOR | BLOWER

- DC Motor
- Motor comes with a built-in overload disconnect for safety and longer motor life

TYPICAL SPECIFICATIONS

- Ceiling ventilator shall have corrosion resistance galvanized steel
- It shall be ducted to a roof vent or wall cap using 4 inch round pipe
- Blower assembly shall be removable, have a centrifugal type blower wheel and a permanently lubricated motor designed for continuous operation
- Includes an attachable non-metallic collar with built-in back draft damper



Comes with protective cardboard cover

Warranty is voided if the cardboard is removed anytime during construction.

Reference	QTY.	Remarks	Project:
			Location:
			Architect:
			Engineer:
			Contractor:
			Submitted by:
			Date:

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.