

# RST Series RST-5

## Features

- 36kA per Phase
- UL 1449 Listed
- 10kA I-nominal Rating
- 200kA SCCR
- 3 Year Standard Warranty



## Product Specifications

### General Specifications

|                                      |                |
|--------------------------------------|----------------|
| Maximum Surge Current Rating Range   | 36kA per Phase |
| UL Type Designation                  | Type 1         |
| UL 1449 I-nominal Rating             | 10kA           |
| UL 1449 Short Circuit Current Rating | 200kA          |

### Design Specifications

|  |
|--|
| Custom MOV design for High Energy Handling in Category C locations |
| Thermally Protected MOVs   |
| External Parallel Connected for Mounting next to Electrical Gear   |
| Reduced Mode of Protection (L1-N, L2-N)                            |

### Diagnostic & Status Monitoring Specifications

|  |
|--|
| LED Protection Status Monitoring (Single LED Standard) |
|--|

### Enclosure

|                                     |
|-------------------------------------|
| Polycarbonate 4.25" x 2.41" x 2.75" |
| Lid ultrasonically sealed           |
| NEMA 4X                             |
| 1/2 inch NPT Side Mount Nipple      |

### Filtering

|    |
|----|
| NO |
|----|

### Physical Specifications

|                       |                                   |
|-----------------------|-----------------------------------|
| Humidity Range        | 0-95% non-condensing              |
| Operating Frequency   | 50-60Hz                           |
| Operating Temperature | -35°C to +85°C                    |
| Typical Connection    | 18" #12 AWG (pre-wired pig tails) |

### UL 1449 Performance Data


| System Voltage   | L-N | L-G | N-G | L-L  | SCCR  | MCOV |
|------------------|-----|-----|-----|------|-------|------|
| 240/120V Split Ø | 700 | -   | -   | 1200 | 200kA | 180  |

## Standards Compliance & Certifications

|   |
|---|
| UL 1449 5th Edition: 2021, cULus, (UL File: VZCA.E316468), ANSI/IEEE C62.41.1-2002, C62.41.2-2002, C62.45-2002, NEC Article 285                     |
| ISO 9001:2014 Quality Management System, ISO 17025:2007 Laboratory Certification (UL DAP Program) Compliance with RoHS, REACH & California Prop 65. |
| 100% Quality Tested prior to shipping   |


RST Series  
**RST-5**

**Model Number Configuration**




\*Flush-Mount (Part #420-0003)  
sold as separate accessory.

**Wiring Configurations**



**Product Diagram**



**Size and Mechanical Specifications**

|                   |                               |
|-------------------|-------------------------------|
| Dimensions        | 4.25" x 2.41" x 2.75"         |
| Weight            | 0.46 lbs                      |
| Enclosure Type    | Polycarbonate NEMA 4X         |
| Installation Type | Indoor / Outdoor              |
| Mounting Method   | Flush / Flange / Through-hole |

