

Product data sheet

Specifications



HomeLine Loadcentre 1PH 200A 120CCT MAIN BREAKER

CHOM60120M200GC

Main

Range of product	Homeline
Product or component type	Loadcentre
[In] rated current	200 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Wall mount
Short-circuit current	22 kA

Complementary

Electrical connection	Lugs
AWG gauge	AWG 4...250 kcmil aluminum/copper
loadcentre type	Main Breaker
Number of spaces	60
Number of circuits	120
Number of tandem circuit breakers	60
Network number of phases	1 phase
Cover type	Combination flush/surface cover
Device composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminum: busbar
Enclosure material	Welded sheet steel
Cover colour	White

Environment

Product certifications	CSA
NEMA degree of protection	NEMA 1 indoor)
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.98 in (15.2 cm)

Package 1 Width	17.01 in (43.2 cm)
Package 1 Length	51.69 in (131.3 cm)
Package 1 Weight	47.0004 lb(US) (21.319 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	112
--	-----

Environmental Disclosure	Product Environmental Profile
--------------------------	---

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	No
--------------------------------------	----

EU RoHS Directive	Compliant
-----------------------------------	-----------

Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations
---------------------	--

Take-back	No
-----------	----