

Model: Whistler
HP241/HP241R/HP241RV



Description:

The Whistler series (HP241, HP241R & HP241RV) of hardhats has a contemporary design, along with economy and comfort. It is versatile to fit a variety of users with their variety of applications. The Whistler series comes with a rain trough and accessory slots. It offers the choice between ratchet or pin-lock adjustments of a nylon-webbing 4-points suspension. It is also available with ventilation holes for hot work environments. The Whistler series is ideal for environments where vertical impact on the head is a risk.

Product Number	Description	Order Multiples	Case Quantity	Case Dimensions	Case Weight
HP241	4-points nylon suspension, pin-lock adjustment, CSA & ANSI Type 1, Class E	12	12	44.5 X 32 X 62.5 cm 17.5" X 12.5" X 24.5"	4.6 kg. 10.1 lbs.
HP241R	4-points nylon suspension, ratchet adjustment, CSA & ANSI Type 1, Class E	12	12	44.5 X 32 X 62.5 cm 17.5" X 12.5" X 24.5"	4.9 kg. 10.8 lbs.
HP241RV	4-points nylon suspension, ratchet adjustment, Ventilation holes, CSA & ANSI Type 1, Class C	12	12	44.5 X 32 X 62.5 cm 17.5" X 12.5" X 24.5"	4.9 kg. 10.8 lbs.

SIZE	N/A	COUNTRY OF ORIGIN	Canada
TYPE	CSA Type 1 & ANSI Type I	MATERIALS	Shell: HDPE Suspension: HDPE/NYLON webbing
CLASSIFICATION	HP241 & HP241R = Class E (dielectric) HP241RV = Class C (conductive)	WEIGHT	HP241R & HP241RV: 392 g HP241: 370 g
COMPLIANCE	CSA Z94.1-15 & ANSI Z89.1-2014	THERMAL RESISTANCE	Softening Temp.: 262°F (128°C)
COMPONENT CLASSIFICATION	N/A	REPLACEMENT SUSPENSION	HP241= HP641S (CSA), HP241S (ANSI) HP241R & HP241RV= HP641RS (CSA), HP241RS (ANSI)
COLOR	White / yellow / orange / dark green / Hi Viz red / light blue / sky blue / navy blue / grey / beige / black / gold / red / Royal blue / north blue / pink / Hi Viz orange / Hi Viz yellow / lime green		

Revision: Jan - 2019

Head Office

2477, Michelin, Laval, Qc H7L 5B9
T: (450) 622-7374 / 1 877 446-3278
F: (450) 622-2243 / 1 877 463-2789

Fall Protection Manufacturing

175 Admiral Blvd., Mississauga, On L5T 2T3
T: (905) 565-9990
F: (905) 565-9906